



OVERVIEW B77 MK III Stereo Tape Recorder

Tape recorder for playback and recording	
Electronic coils (wound in-house at Revox KLANGWERK)	
Balanced XLR input/output	New
Completely revised audio electronics	New
Electronic balancing input/output	
Use of high-quality film capacitors instead of conventional electrolytic capacitors in the audio electronics	New
Switch for CCIR/NAB equalization switching	New
Output level setting	
Input level setting	
Switching option 7 1/2 15 IPS (19/38)	
Possibility to switch between different magnetization during playback and recording 19 cm/sec = standard Revox 257 nWb/m 38 cm/sec = 320 nWb/m and 510 nWb/m (can also be individually adjusted in the device via potentiometer)	New
Optimized playback of LPR90 long playback tape and SM900 studio tape	New
Headphone connection DC-coupled, bipolar (film capacitors)	New
Digital totalizer Mode 1: Counter Mode 2: Time	New
Original winding motors with ball bearings	
Original Capstan motor with ball bearing	
Improved original Revox pickups - further optimized for longer durability	
Accessories included: XLR-RCA/Cinch adapter	New
Optionally available for multiuser integration: Multiuser Adapter Global Cache	
Coil size pushbutton	
Cutter slide button	
PAUSE	
Rewind	
Fast forward	
PLAY	
STOP	
RECORD	
Volume control	
Level indicator LEFT CHANNEL	
Level indicator RIGHT CHANNEL	
TAPE/Input switch Monitor (rear band control)	
Operating mode switch Monitor	
Recording preselection switch REC L, ON/OFF	
Recording light indicator, left channel	
Input level control INPUT LEVEL left channel	
Input level control INPUT LEVEL right channel	
Recording preselection switch REC R, ON/OFF	
Recording light indicator, right channel	
Overload indicator, left channel	
Overload indicator, right channel	



OVERVIEW B77 MK III Stereo Tape Recorder

Microphone input R / L	
Input selector switch left channel	
Input selector switch right channel	
MIC LO	
MIC HI	
OFF	
LINE	
Voltage selector LINE Voltage Selector	
Mains connection AC POWER	
FUSE mains fuse	
Connection for external belt speeds CAPSTAN SPEED	
Connection for TAPE DRIVE drive remote control	
Band limit switch with infrared light barrier	

Specifications:

Size :	W 452 x H 414 x D 207 mm
Weight:	17 kg